



X2 extreme 7 12V

7" Rugged HMI with iX runtime

800 × 480 pixel (16:9)

TFT-LCD touch screen

1.5 GB application memory

Ethernet 1x100 Mbit

-30°C to +70°C operating temperature

DNV GL, KR, LR, ABS, CCS, BV, NK, RS marine approvals

UL Class I Div 2, ATEX/IECEX Zone 2,22

Facts

General description

Part number	640014005
Life cycle status	Active
Warranty	2 year

Certifications

General	CE, FCC, KCC, UL 61010-2-201, UL 746C
Hazardous	ULC1D2, ATEX (Zone2), ATEX (Zone22), IECEx (Zone2), IECEx (Zone22)
Marine	KR, LR, ABS, CCS, BV, NK, DNV GL, RS

Mechanical

Mechanical size	204 x 143 x 62mm
Mounting option	Panel Mount
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	189 x 128mm
Weight	0.8 kg
Housing material	Powder-coated aluminum, Black

Power

Input voltage	12 V DC (9 to 16 VDC)CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4.UL and cUL: The power supply must conform with the requirements for class 2 power supplies.
Power consumption (max)	11 W
Input fuse	Internal DC fuse

Serial communication

Number of serial ports	1 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/RS485/CAN

Ethernet communication

Number of Ethernet ports	1
Ethernet port 1	1x10/100 Base-T (shielded RJ45)

Communication CAN

Number of CAN ports	1
CAN port 1	1 Mbit

Expansion interface

SD card	SD and SDHC
USB	2xUSB 2.0 500mA

System

Hardware platform	X2 extreme
CPU	i.MX6DualLite, Dual Cortex-A9 800MHz 512kBL2cache
RAM	1 GB
FLASH	2GB SSD(eMMC), 1.5GB free for application

Display

Size diagonal	7" diagonal
Resolution	800x480 pixels
Backlight	LED Backlight
Backlight life time	50000 hours
Backlight brightness	500 cd/m2
Backlight dimming	Marine optimized dimming
Display type	TFT-LCD with LED backlight

Environmental

Operating temperature	-30°C to +70°C
Storage temperature	-40°C to +80°C
Shock	40g, half-sine, 11ms according to IEC60068-2-27
Vibration	4g, according to IEC 60068-2-6, Test Fc
Sealing front	IP66, NEMA 4X/ 12 and UL Type 4X/ 12
Sealing back	IP20
Humidity	5% – 95% non-condensed
Altitude (max)	< 3000m