



X2 pro 10 web

10" web client HMI

1024 × 600 pixel (16:9) TFT-LCD touch screen

TFT display

8GB EMMC

Ethernet 2x100 Mbit

-10°C to +60°C operating temperature

DNV GL, KR, LR, ABS, CCS, BV, NK marine approvals

CE, FCC, KCC, UL approvals

Facts

General description

Part number	630023605
Life cycle status	Active
Warranty	2 year

Certifications

General	CE, FCC, KCC, UL 61010-2-201
Marine	KR, LR, ABS, BV, CCS, NK, DNV GL

Mechanical

Mechanical size	292 x 194 x 52mm
Mounting option	Panel Mount, VESA 75 x 75
Number of touches	1 million finger touch operations
Touch type	Resistive
Cut-out size	275 x 177mm
Weight	1.65 kg
Housing material	Powder-coated aluminum, Gray

Power

Input voltage	24 VDC (18 to 32 VDC) CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4. UL and cUL: The power supply must conform with the requirements for class 2 power supplies.
Power consumption (max)	21.6W
Input fuse	Internal D

Display

Size diagonal	10.1" diagonal
Resolution	1024x600 pixels
Backlight	LED Backlight
Backlight life time	50000 hours
Backlight brightness	500 cd/m2
Backlight dimming	Dimming in system menu
Display type	TFT-LCD with LED backlight

Serial communication

Number of serial ports	1 Port 9pin DSUB
Serial port 1	Not in use
Serial port 2	Not in use
Serial port 3	Not in use

Ethernet communication

Number of Ethernet ports	2
Ethernet port 1	1x10/100 Base-T (shielded RJ45)
Ethernet port 2	1x10/100 Base-T (shielded RJ45)

Expansion interface

SD card	SD and SDHC
USB	2xUSB 2.0 500mA

Sign up to our monthly Newsletter!



Subscribe now

System

Hardware platform	X2
CPU	i.MX6Quad, Quad ARMCortex-A9 1.0GHz 1M BL2 cache
RAM	2 GB
FLASH	8GB EMMC

Software

Operating system	Linux
Web browser	Chromium in Kiosk mode

Environmental

Operating temperature	-10°C to +60°C
Storage temperature	-20°C to +70°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP65, NEMA 4X/ 12 and UL Type 4X/ 12
Sealing back	IP20
Humidity	5% – 85% non-condensed
Altitude (max)	< 3000m

Sign up to our monthly Newsletter!